



INFICON EDC Inc. *Quality Quartz Crystals and Oscillators*


EC 52
Series
HCMOS
SMD Clock Oscillators

Features: 2.5 x 3.2 mm, 3.0, 2.5 & 1.8 V, CMOS Compatible, Seam Seal Metal Lid

PARAMETERS	EC521	EC522
Package Part#	S620	
Frequency Range (MHz)	0.5 ~ 75	
Frequency Stability (\pm ppm)	50	
Temperature Range ($^{\circ}$ C)	Operating - 0 ~ +70 / Storage - -55 ~ +125	
Supply Voltage (V)	2.5 \pm 5%	1.8 \pm 5%
Supply Current (mA)	5 ~ 14 (Freq. Dependent)	5 ~ 14 (Freq. Dependent)
Rise & Fall Time (nS)	10 Max	
Startup Time (mS)	10 Max	
Output "0" / "1" Level (V)	10% of Vcc Max / 90% of Vcc Min	
Symmetry (Duty Cycle) (%)	40 / 60 STD (45 / 55 Available)	
Output (CMOS)	15 pF	
Tristate Function	With	

STANDARD AVAILABLE OPTIONS

Frequency Stability (\pm ppm): 20, 25, 30, 100
 Operating Temp. Range ($^{\circ}$ C): -20 ~ +70, -30 ~ +75, -40 ~ +85



INFICON EDC Inc. • (800) EDC-XTAL • www.inficonedc.com

This drawing & information are the property of INFICON EDC Inc. and shall not be reproduced, copied or used in any manner without the sole permission of INFICON EDC Inc. All specification subject to change. Please contact factory for current specifications (Rev. 05/08)