



INFICON EDC Inc. *Quality Quartz Crystals and Oscillators*

EX 45
Series
COMMERCIAL
SMD Crystal

Features: *Commercial, Industrial, Custom Made-to-Order, HC-45 Gull-Wing Series*

PARAMETERS	EX451	EX452	EX453
Package Part#		S140	
Frequency Range (MHz)	12.0 ~ 40.0	42.0 ~ 100.0	60.0 ~ 150.0
Overtone	Fundamental	3 rd	5 th
Frequency Calibration (\pm ppm)		50	
Frequency Stability (\pm ppm)		50	
Operating Temp. Range ($^{\circ}$ C)		0 ~ +70	
Max. Resistance Level (Ω)		Frequency Dependent	
Resonance Type		Series or Load (Specify 10 ~ 50 pF)	
Max. Drive Level (μ W)		500	
Test Drive Level (μ W)		50	


STANDARD AVAILABLE OPTIONS

Frequency Calibration (\pm ppm): 10, 15, 20, 25

Frequency Stability (\pm ppm): 10, 15, 20, 25, 30 (Frequency and Temp. Range Dependent)

Operating Temp. Range ($^{\circ}$ C): Downward to -40 and Upward to +105 (Frequency Range Dependent)

Max. Resistance Level (Ω): Lower values are available (Frequency Range Dependent)



INFICON EDC Inc. • (800) EDC-XTAL • www.inficonedc.com

This drawing & information are the property of INFICON EDC Inc. and shall not be reproduced, copied or used in any manner without the sole permission of INFICON EDC Inc. All specification subject to change. Please contact factory for current specifications (Rev. 05/08)